



Alto Hi-wall Inverter Air Conditioner



Find out more at www.greeac.com.au

Enjoy comfort with your family



The Alto Series of air conditioners lets you indulge in ultimate tranquillity within your home. This compact stylish, and elegant series is specifically designed to offer reliable and energy-efficient comfort for you and your family throughout the year. Available in sizes from 2.0kW to 10.0kW.

Energy Efficiency

The Gree Alto range of air conditioners offers energy efficient operation all year round. Gree's G10 inverter technology allows for fast attainment of ultimate degrees and when coupled with the Turbo and I-Feel modes, Alto can deliver the perfect environment.

Convenient Operation

Take control with ease using the Alto's built-in smart Wi-Fi functionality. By using the Gree+ app, you can conveniently operate your Alto air conditioner from your mobile device or tablet. Stay connected and experience the convenience of smart control with the Alto series.

Home Comfort

- Enjoy customisable airflow with a multi speed fan
- Easily adjust settings with the adjustable LED display for added convenience
- Maintain clean and fresh air with washable dust filters that are easy to clean



Reliable Function

The Alto series is the first Gree series to benefit from the new automated manufacturing factories being built by Gree. Utilising intelligent robots and production machines, the Alto series benefits from a tireless computer-controlled manufacturing process that for some processes achieves an 85% self-production/automation rate. These new production facilities fully test every unit prior to despatch, ensuring quality, reliability and peace of mind for the homeowner.

Features



Wifi Control



Comfortable Sleep Curves



Auto Restart



LED Display



Timer



Intelligent Defrosting



Auto Clean



Turbo Button



3D Airflow*



R32 Refrigerant



I Feel



Energy Saving




Dred



Self-Diagnosis



Dehumidifying



Healthy Filters

*3D Airflow limited to specific models. Please confirm with supplier.

Model		GWH07ATAXA-K6DNA1D/I	GWH09ATBxB-K6DNA1C/I	GWH12ATCXB-K6DNA1B/I	GWH18ATDXD-K6DNA1C/I	GWH24ATEXF-K6DNA1E/I	GWH28ATEXF-K6DNA1A/I	GWH36AWFXH-K6DNA1A/I
		GWH07ATAXA-K6DNA1D/O	GWH09ATBxB-K6DNA1C/O	GWH12ATCXB-K6DNA1B/O	GWH18ATDXD-K6DNA1C/O	GWH24ATEXF-K6DNA1E/O	GWH28ATEXF-K6DNA1A/O	GWH36AWFXH-K6DNA1A/O
Performance								
Cooling Capacity (Range)	kW	2.00 (0.5~2.8)	2.7 (0.66~3.4)	3.52 (0.5~4.5)	5.2 (0.8~6.3)	7.1 (2.5~8.5)	8.2 (3.3~9.67)	10 (2.3~11.7)
Heating Capacity (Range)	kW	2.64 (0.6~3.15)	3.00 (0.8~3.8)	3.8 (0.9~4.8)	5.8 (1.0~6.5)	7.8 (2.0~8.6)	9.0 (3.0~10.14)	11.7 (3.8~12.4)
Cooling Power Input	kW	0.54	0.72	0.91	1.53	1.92	2.44	2.73
Heating Power Input	kW	0.68	0.77	0.97	1.57	2.0	2.65	3.24
Cooling AEER	W/W	3.67	3.72	3.85	3.35	3.66	3.28	3.636
Heating ACOP	W/W	3.87	3.88	3.9	3.65	3.86	3.39	3.374
SERL Star Label	Cool	3/3/3	3.5/3/3.5	4.5/4/4	3.5/3/3.5	5.5/4.5/4.5	4/3.5/3.5	4.5/4/4
Hot/Ave/Cold	Heat	2.5/2/1.5	3/2/1.5	3/2.5/2	3/2.5/2	3.5/2.5/2	3.5/2.5/2	4/3/2
Dehumidifying Volume	L/Hr	0.6	0.8	1.6	1.8	2.5	3	3.5
Air Flow Volume (Max)	L/Sec	139	153	180	278	375	347	491
Sound Pressure (Min/Max) Ind	dB(A)	22/38	22/40	20/43	27/47	30/53	30/52	34/57
Sound Power (Min/Max) Ind	dB(A)	36/54	36/56	34/60	40/60	45/68	46/68	48/71
Sound Pressure/Power Out	dB(A)	50/60	51/61	52/65	56/65	60/69	61/69	62/71
Electrical								
Power Supply (Outdoor)	V/Hz/Ph	220~240 / 50 / 1						
Recommended Circuit Breaker	A	10	10	10	16	25	25	25
Nominal Current (Cool/Heat)	A	2.4/3	3.54/3.77	4.4/4.6	7.2/6.3	8.4/8.8	11/11.7	12.0/14.0
Control Wiring	3 Core plus Earth (4 Cores)							
Dimensions and Weights								
Indoor Dimensions (WxHxD)	mm	708x260x185	783x260x185	835x275x200	943x333x246	1078x333x246	1078x333x246	1350x333x253
Indoor Net Weight	kg	7.0	8.0	8.5	13.0	15.0	15.0	20.0
Outdoor Dimensions (WxHxD)	mm	710x450x293	732x555x330	732x555x330	802x555x350	958x660x402	958x660x402	1000x746x427
Outdoor Net Weight	kg	21.5	24.5	27.5	31.5	42.0	45.5	55.5
Installation								
Operating Temp Range Cool	°C	-15° ~ 52	-15° ~ 52	-15° ~ 52	-15° ~ 52	-15° ~ 52	-15° ~ 52	-15° ~ 52
Operating Temp Range Heat	°C	-15° ~ 24	-15° ~ 24	-15° ~ 24	-15° ~ 24	-15° ~ 24	-15° ~ 24	-15° ~ 24
Refrigerant Type		R32	R32	R32	R32	R32	R32	R32
Refrigerant Charge	kg	0.45	0.5	0.75	0.9	1.2	1.4	1.9
Max Pipe Length (pre-charged)	M	15 (10)	15 (10)	20 (10)	25 (10)	40 (10)	40 (10)	70 (10)
Max Height	M	10	10	10	10	25	25	50
Additional Refrigerant	g/m	16	16	16	16	16	16	16
Pipe Connection	mm	1/4" ~ 3/8"	1/4" ~ 3/8"	1/4" ~ 3/8"	1/4" ~ 1/2"	1/4" ~ 1/2"	1/4" ~ 1/2"	1/4" ~ 1/2"

Note: Above parameters are for reference only. Actual parameters may vary.



For Installation and Sales:

For Parts and Warranty:

GREE
AIR CONDITIONERS

www.greeac.com.au